

NOTE: Read Instructions carefully before installing.

1. Remove both the front and rear fairing side moldings from the left and right sides of the bike, as shown in fig. A. Using a thin-bladed screwdriver, prey center area out and push trim to rear, and pull back and out from center. **(See fig. a)**

2. Remove the two (2) Phillips head screws from front molding and one (1) Phillips head screw from rear molding on both sides of bike. (See fig. a)

3. Remove molding caps from both sides of fairing as shown in Fig. B. Remove both Phillips head screws. **(See fig. B)**

4. Remove stock Phillips head screws from both right and left side fairing lowers (air dam). **(See arrow C)**

5. Remove stock Phillips head screw from center air dam. **(See Arrow D) NOTE:** With all screws removed, the lower fairing and air dam will go down about 1-2 inches.

6. Remove stock Phillips head screw holding turn signal canceling tab, located above radiator grill in center, behind black plastic fork air deflector. **(See Arrow E)**

7. Using 8mm wrench, remove stock radiator grill frame with screen mounting acorn nuts located at top on left and right sides. **(See Arrow F)**


8. Remove stock radiator grill frame with screen by lifting left and right lower tabs up and then out.


9. With stock radiator frame with screen removed, position radiator grill centered over stock screen as shown in **Fig. G.**

10. Using Phillips head screws, tinnerman clips and rear mounting brackets supplied, attach radiator grill to screen as shown in **Fig. G.** Tighten mounting hardware securely. **NOTE:** Don't over tighten.

11. Reinstall assembled grill and frame with screen onto the motorcycle by reversing steps used to remove stock grill frame with screen.

NOTE: Before riding bike, be sure to check that all mounting hardware is properly reinstalled and tightened securely.





133 Gold St, Worcester, MA 01608 Ph: 508-793-2919 800-821-9861 Fx: 508-793-2919 www.addonaccessories.net info@addonaccessories.net